

# GROUND MOVING

- Extremely tough and rugged
- 30° angle
- Heavy cylinders
- Bolt-on reversible blade made of steel HBW450
- Coupling for skid loader




## DOZER BLADE




Hydraulic hoses with quick couplings

Shockproof valve



## TILT DOZER BLADE



## LEVELING BOX DOZER BLADE



Hydraulic hoses with quick couplings

Shockproof valve

1/2" electrovalve

Hydraulic oscillation +/- 8°

Standard electric kit


Proportional distributor

Rear pad with hydraulic control which neutralizes the riding effect

Laser control system

Bolt-in blade

Standard electric kit



## DIMENSIONS

		DB 150	DB 180	DB 210	DB 240	DB 270
A	<b>Width</b>	1510	1810	2110	2410	2710
B	<b>Depth</b>	600	600	600	600	600
C	<b>Height</b>	730	730	730	730	730

- It is equipped with shockproof valve
- Bolt-on blade made of steel 450HBW

The M3 dozer blade can be easily fitted to any kind of skid steer loader, wheel loader and telehandlers up to 80HP.

It is equipped with shockproof valve, hydraulic angle  $\pm 30^\circ$ , hydraulic hoses, bolted bracket in wear-resistant steel 450 HBW and coupling to SSL.



MODEL	DB 150	DB 180	DB 210	DB 240	DB 270
Working width [mm]	1299	1560	1820	2075	2330
Weight [kg]	340	370	400	420	450
Hydraulic blade inclination R/L	±30°	±30°	±30°	±30°	±30°

