

GROUND LEVELLING

- Extremely tough and rugged
- Heavy cylinders
- Pneumatic floating wheels for high adaptability to the ground
- Coupling to the machine

GRADER BLADE



- On/off distributor
- ST52 steel structure
- Manual flow regulator
- Electrical control kit



DUAL GRADER BLADE




- Proportional and on/off distributor
- It works both as a grader blade and as a tilt dozer blade
- Double bevel curved blade
- Over center valve on wheel lifting cylinder



Control joystick







DIMENSIONS

		GR 230	GR 250	GR 270
A	Width	2300	2500	2700
B	Depth	2360	2360	2360
C	Height	1480	1480	1480

The Grader Blade M3 can be fitted to small skid steer loaders with power ranging from 50 to 120 HP. It is ideal for the preparation and the leveling of lands, roads and yards. It is equipped with the tilt system 32°, oscillation 40° and shift 450 mm of the blade with hydraulic functioning through a control panel, manual flow regulator on the distributor on / off, ST52 steel structure, coupling to the machine, hydraulic hoses and electric control kit.

OPTIONALS

	Laser Control System (1)	Proportional distributor (2)		
Left/right closing plate (3)				



MODEL	GR 230	GR 250	GR 270
Blade width [mm]	2300	2500	2700
Weight [kg]	670	690	710
Hydraulic blade inclination R/L	±38°	±38°	±38°
Hydraulic blade oscillation R/L	±32°	±32°	±32°
Hydraulic blade translation [mm]	±450	±450	±450

