



## **DIMENSIONS**

	· · · · · · · · · · · · · · · · · · ·		
	MC 120	MC 160	MC 180
Width	1265	1725	1875
Depth	220	220	220
Heiaht	365	365	365

- Mechanical shock absorber
- Hirth coupling
- Blades protection
- Orbital motor protected by anti-shock and anti-cavitation valve

The hedge trimmer M3 MC series can be fitted to mini excavators and is suitable to cut hedges (light pruning) up to a maximum  $\emptyset$  of 3 cm.

The blades are in wear resistant steel. It is equipped with hirth coupling, orbital motor protected by anti-shock and anti-cavitation valve, mechanical shock absorber and blades protection, direct coupling to the machine. Adapters for quick hitch are available upon request.

## **OPTIONALS**

Spare blades kit	Hydraulic hoses kit











≝
_
盗
Σ
2
골
ত
HEDGE
Ē

MODEL	MC 120	MC 160	MC 180
Weight [kg]	42	55	64
Max pressure [bar]	180	180	180
Max flow rate [L/min]	26/40/50	26/40/50	26/40/50
Excavator class [T]	1,0 - 5,0	2,0 - 5,0	2,0 - 5,0
Working width [mm]	1200	1600	1800
Max cutting diameter [mm]	30	30	30

