



DIMENSIONS

		MH9 70HD2	MH9 90HD2	MH9 105HD2	MH11 130HD2	MH13 105HD2	MH13 130HD2	MH15 130HD2	MH15 160HD2
A	Width	850	1050	1250	1450	1250	1450	1600	1900
B	Depth	800	800	800	900	950	950	800	800
C	Height	600	600	600	600	850	850	850	850

The Hydraulic Mulcher M3 is designed with a strong and reliable structure and can easily fit any type of excavators. It is manufactured in different models, depending on the use and size of the excavator. It is supplied complete with hydraulic motor (piston motor from the MH15 series), anti-cavitation valve, priority shockproof valve, adjustable support slides and drilled flat plate. **Drain is recommended for counter-pressures > 5 bar.** Rotation speed 2200/2500 rpm.

OPTIONALS

	Floating system	Hydraulic hoses
Support roller	Bracket	





MODEL	MH9 70HD2	MH9 90HD2	MH9 105HD2	MH11 130HD2	MH13 105HD2	MH13 130HD2	MH15 130HD2	MH15 160HD2
Working width [mm]	700	900	1050	1300	1050	1300	1300	1600
Weight [kg]	220	330	400	440	580	650	920	1020
Oil flow [L/min]	40/50/60/80/90	40/50/60/80/90	50/60/80/90	60/80/90	70/80/90	70/80/90	100/125/160	100/125/160
Pression [bar]	200/220	200/220	200/220	200/220	200/220	200/220	200/250	200/250
Excavator class [T]	5,0-8,0	6,0-8,0	6,0-12,0	8,0-12,0	10,0-16,0	10,0-16,0	12,0-25,0	15,0-25,0
Rotor standard	MHF17	MHF17	MHF17	MHF19	MHF19	MHF19	MHF11	MHF13
Rotor optional	*****	*****	*****	*****	*****	*****	MHF10	MHF12
Motor displacement [cc]	22/27/34/44/51	22/27/34/44/51	27/34/44/51	44/51	44/51	44/51	32/64	32/64
Motor type	gears			cast iron gear motor*			piston motor	
Hammers number [n°]	12	18	22	18	16	18	26	32

* Upon request, a piston motor is available too