



DIMENSIONS

		MH9 70HD3	MH9 90HD3	MH9 105HD3	MH13 105HD3	MH13 130HD3	MH15 130HD3	MH15 160HD3	MH20 130HD3	MH20 160HD3
A	Width	850	1050	1250	1250	1450	1600	1900	1700	2000
B	Depth	800	800	800	950	950	800	800	1000	1000
C	Height	600	600	600	850	850	850	850	900	900

The Hydraulic Mulcher HD3 M3 is designed with a strong and reliable structure and can easily fit any type of excavators. It is manufactured in different models, depending on the use and size of the excavator. It is supplied complete with hydraulic motor (piston motor from the MH15 series), anti-cavitation valve, priority shockproof valve, adjustable support slides and drilled flat plate. **Drain is recommended for counter-pressures > 5 bar.** Rotation speed 2200/2500 rpm.

OPTIONALS

	Floating system	Hydraulic hoses
Bracket	Support roller	





MODEL	MH9 70HD3	MH9 90HD3	MH9 105HD3	MH13 105HD3	MH13 130HD3	MH15 130HD3	MH15 160HD3	MH20 130HD3	MH20 160HD3
Working width [mm]	700	900	1050	1050	1300	1300	1600	1300	1600
Weight [kg]	340	400	460	685	745	950	1050	1050	1185
Oil flow [L/min]	40/50/60/80/90	50/60/80/90	50/60/80/90	80/90	80/90	100/125/160	100/125/160	100/130/180	100/130/180
Pression [bar]	200/220	200/220	200/220	200/220	200/220	200/250	200/250	200/350	200/350
Class escavatore [t]	5,0-12,0	6,0-12,0	6,0-12,0	10,0-16,0	10,0-16,0	12,0-25,0	16,0-25,0	16,0-30,0	18,0-30,0
Rotor standard	MHF14	MHF14	MHF14	MHF14	MHF14	MHF14	MHF14	MHF14	MHF14
Rotor optional	MHF15	MHF15	MHF15	MHF15	MHF15	MHF15	MHF15	MHF15	MHF15
Motor displacement [cc]	22/27/34/44/51	27/34/44/51	27/34/44/51	44/51	44/51	32/64	32/64	45/60/80	45/60/80
Motor type	gears			cast iron gear motor*			piston motor		
Hammer number [n°]	18	24	30	30	36	36	42	36	42

* Upon request, a piston motor is available too