



DIMENSIONS

		PPF S10-10	PPF S10-12	PPF S18-10	PPF S18-12	PPF S20-12	PPF 18-12	PPF 20-12	PPF 25-12	PPF 35-12	PPF 45-12	PPF 60-12	PPF 80-12	PPF 120-12
A	Width	1200	1200	1200	1200	1500	1500	1500	1500	1500	1500	1500	1500	1500
B	Depth	1000	1200	1000	1200	1200	1200	1200	1200	1200	1200	1200	1200	1200
C	Height	920	920	920	920	970	415	415	415	515	515	645	645	645

- The version for skid steer loader is equipped with protection grid

The Fork Carriage M3 can be attached to any type of skid steer loader, backhoe and wheel-loader, telehandler or excavator Available in various lifting capacities ranging from 1.000 KG up to 12.000 KG with both forks. Upon request available also with lifting capacity up to 30.000 kg. The version

for skid steer loader (PPF SXX) is equipped with protection grid.

OPTIONALS

Hydraulic side shifter



MODEL	PPF S10-10	PPF S10-12	PPF S18-10	PPF S18-12	PPF S20-12	PPF 18-12	PPF 20-12	PPF 25-12	PPF 35-12	PPF 45-12	PPF 60-12	PPF 80-12	PPF 120-12
Working width [mm]	1200	1200	1200	1200	1500	1500	1500	1500	1500	1500	1500	1500	1500
Forks dimensions [mm]	80x30x1000	80x30x1200	100x35x1000	100x35x1200	120x35x1200	100x35x1200	120x35x1200	120x40x1200	120x45x1200	120x50x1200	150x60x1200	200x60x1200	200x70x1200
Load capacity [kg]	1000	1000	1800	1800	2000	1800	2000	2500	3500	4500	6000	8000	12000
Weight** [kg]	150	160	170	180	420	195*	215*	230*	290*	305*	*****	*****	*****



SIDESHIFT

* weight without machine coupling / ** weight without hydraulic side shifter